

## Product Highlights

### Global Mobile Broadband

3G/4G mobile connectivity lets you take your broadband connection with you wherever you go

### Wireless AC and Gigabit Ethernet

Stream HD multimedia across your home without interruption, using the fastest wired and wireless technologies available today

### Simple, secure setup

Set up the DWR-956M in no time with the web-based setup wizard, and create secure wireless connections easily using Wi-Fi Protected Setup (WPS)



## DWR-956M

# Fibre/LTE Wi-Fi AC1200 Dual Band GE Router with SIP, VoIP, VoLTE, CS & Fax support

## Features

### Connectivity

- Supports multiple WAN connections for flexibility, redundancy, and future connectivity
- Built-in LTE and ETH WAN for connecting to your high-speed broadband Internet connection
- 1 x Gigabit WAN port support high-speed Internet connections of today and tomorrow
- 4 x Gigabit LAN ports to connect wired devices for high-speed online activities
- Wireless 802.11ac for high speed connections to all your PC's and mobile devices
- 1 x USB 2.0 port to share media

### Security

- Wi-Fi Protected Setup (WPS) to quickly and securely add devices to your network
- WPA/WPA2 encryption to secure your wireless traffic

### Ease of Use

- Quick Setup Wizard

The DWR-956M Fibre / LTE AC1200 GE Router with VoIP, VoLTE, CS & Fax is a highly integrated router with everything your home or small business needs for high-speed internet access. It combines a Gigabit Ethernet Internet Port, 4G mobile Internet support, Voice over IP (VoIP), Voice over LTE (VoLTE), Circuit Service (CS) and Fax with Gigabit wireless together in a single, easy to use product that shares an internet connection for all your devices.

## Fast and Reliable Home Network

The D-Link DWR-956M Fibre / LTE Router creates a blazing fast home network that connects all of your devices to your broadband Internet connection. Concurrent dual-band 802.11ac brings you the future of high-bandwidth wireless connectivity, allowing you to stream HD video, make Internet voice calls, VoLTE and CS phone calls and surf the Internet from every corner of your home without interruption. Gigabit Ethernet ports provide high-speed wired connections for up to four PCs or other devices. It's stylish, easy to use, and provides you with a reliable network for today and tomorrow.

## Multiple Failover Redundancy and Future Connectivity

The D-Link DWR-956M Fibre / LTE Router comes not only with a built-in high-speed CAT 4 LTE and Gigabit Ethernet WAN port. This means that if your primary connection method should fail, the DWR-956M will automatically fallback to your pre-defined backup connection.

## Voice over IP

The DWR-956M provides Voice over IP technology with advanced communication features, and is compatible with industry-wide phone services so you can make and receive calls reliably. Use the FXS phone port on the DWR-956M to connect an ordinary phone set for your VoIP phone calls, and use the router functions to connect all of your family members or personal to the Internet for a fast and secure online experience throughout your home or office.

# DWR-956M Fibre/LTE AC1200 Gigabit Router with SIP, VoIP, VoLTE, CS& Fax

## Smooth Streaming with Wireless AC

The DWR-956M uses the latest Wireless AC technology, which provides transfer rates of up to 1.2Gbps (866AC + 300N). The router operates on both the 2.4 GHz and 5GHz wireless bands at the same time using concurrent dual-band technology and three external antennas. This allows you to browse the web, chat and e-mail using the 2.4 GHz band, while simultaneously streaming digital media, playing online games, or making Internet voice calls on the 5GHz band.

## Designed for Optimal Wireless Coverage

The DWR-956M's antennas have been carefully designed to ensure that you will get little to no dead space in any environment. The high-powered Amplifier sends the signal into the farthest corners of your home. Furthermore, the DWR-956M's multiple external antennas improve wireless reception by bringing signals to where they are most needed to achieve the best possible performance.

## File Sharing Right at Your Fingertips

The DWR-956M lets you connect a USB storage device and instantly share documents, movies, pictures, and music. You can put your music library on a USB drive and share it with your entire home. You can show photos on the living room TV while a family member watches a movie on their computer. You can stream media files to multiple devices without interruption, or save them to your device for offline playback. The intuitive interface lets anyone immediately connect to a variety of entertainment options stored securely on your own storage device.

## Easy to Set Up and Secure

Setting up the DWR-956M is easy with the D-Link setup wizard. Simply open the setup utility and follow a few easy steps to get your home network up and running. You can also set up a secure network with the touch of a button using Wi-Fi Protected Setup (WPS). Simply press the respective WPS button on each device to instantly establish a secure connection to a new device. Rest assured that your network is secure with WPA/WPA2 wireless encryption and built-in dual active firewalls (SPI and NAT), so you can shop online and do your online banking with confidence.

## Secure and Smooth Transmissions

The DWR-956M has built-in dual active firewalls (SPI and NAT), so you can shop online and do your online banking with confidence. It is also equipped with WPA wireless security and access control to protect your network from unauthorized access and outside threats so you can use the Internet with confidence. In addition, QoS priority queues and packet prioritization minimize traffic congestion and deliver smooth VoIP and streaming media, providing you with the best possible Internet experience.

Technical Specifications			
Device Interfaces	<ul style="list-style-type: none"> <li>4 x 10/100/1000 Gigabit LAN Ports</li> <li>1 x 10/100/1000 Gigabit WAN Port</li> <li>1 x FXS VoIP / VoLTE / CS Ports</li> <li>802.11ac/n/g/b Wireless LAN<sup>1</sup></li> <li>CAT4 LTE (Qualcomm solution)</li> <li>1 x USB 2.0 Port</li> </ul>	<ul style="list-style-type: none"> <li>Power Button</li> <li>WPS Button</li> <li>Reset Button</li> </ul>	
Antenna Configuration	<ul style="list-style-type: none"> <li>2 x 5dBi detachable external LTE antennas</li> <li>2 x 5dBi Fixed external Wi-Fi Antennas</li> </ul>		
Data Signal Rate	<ul style="list-style-type: none"> <li>2.4GHz</li> <li>300Mbps<sup>1</sup></li> </ul>	<ul style="list-style-type: none"> <li>5 GHz</li> <li>866 Mbps<sup>1</sup></li> </ul>	<ul style="list-style-type: none"> <li>LTE</li> <li>DL150 Mbps UL 50 Mbps</li> </ul>

# DWR-956M Fibre/LTEAC1200 Gigabit Router with SIP, VoIP, VoLTE, CS & Fax

Standards	<ul style="list-style-type: none"> <li>• IEEE 802.11ac</li> <li>• IEEE 802.11n</li> <li>• IEEE 802.11g</li> <li>• IEEE 802.11b</li> </ul>	<ul style="list-style-type: none"> <li>• IEEE 802.3</li> <li>• IEEE 802.3u</li> <li>• IEEE 802.3ab</li> <li>• IEEE 802.3az</li> <li>• IEEE 802.3x</li> </ul>
Network Protocols	<ul style="list-style-type: none"> <li>• RFC2516 PPP over Ethernet (PPPoE)</li> <li>• RFC1662 PPP in HDLC-like Framing</li> <li>• RFC1332 PPP Internet Protocol Control Protocol</li> <li>• Support ALG (Application Level Gateways)</li> <li>• DHCP Client</li> </ul>	
DWR-956M/A	<ul style="list-style-type: none"> <li>• WCDMA: B1/5/8</li> <li>• FDD LTE: B1/B3/B5/B7/B8/B20</li> <li>• GSM: 850/900/1800/1900</li> <li>• TDD LTE: B38/B40</li> </ul>	
DWR-956M/B	<ul style="list-style-type: none"> <li>• TDD LTE: B42/B43</li> </ul>	
Security	<ul style="list-style-type: none"> <li>• WPA &amp; WPA2 (Wi-Fi Protected Access)</li> <li>• Wi-Fi Protected Setup (WPS) - PIN/PBC</li> </ul>	
Advanced Features	<ul style="list-style-type: none"> <li>• Multi-language Web Setup Wizard</li> <li>• UPnP support</li> <li>• Multiple PVC (up to 8)</li> </ul>	<ul style="list-style-type: none"> <li>• Dual Active Firewall</li> <li>• VPN pass-through/multi-session PPTP/L2TP/IPSec</li> <li>• 802.1p QoS</li> </ul>
Routing Features	<ul style="list-style-type: none"> <li>• RFC768 User Datagram Protocol (UDP)</li> <li>• RFC791 Internet Protocol (IP)</li> <li>• RFC792 Internet Control Message Protocol (ICMP)</li> <li>• RFC793 Transmission Control Protocol (TCP)</li> <li>• RFC826 An Ethernet Address Resolution Protocol (ARP)</li> <li>• RFC862 Echo Protocol</li> <li>• Support IP routing</li> <li>• Support transparent bridging</li> </ul>	<ul style="list-style-type: none"> <li>• Support source and destination routing</li> <li>• Support DHCP server/client</li> <li>• Support UPnP</li> <li>• Support NAT, NAT</li> <li>• Support DMZ</li> <li>• Support IP QoS</li> <li>• Support IGMP proxy</li> <li>• Support IPv6</li> </ul>
Management Features	<ul style="list-style-type: none"> <li>• Device Configuration, Management and Update</li> <li>• Web based GUI</li> <li>• Command Line Interface via serial port, telnet, or SSH</li> <li>• Universal Plug and Play (UPnP) Internet Gateway Device</li> </ul>	<ul style="list-style-type: none"> <li>• WAN Management Protocol (TR-069)</li> <li>• SNMP v1/v2</li> <li>• PSI configuration file upload and download</li> <li>• Date/time update from SNTP Internet Time Server</li> </ul>
DSP Feature list	<ul style="list-style-type: none"> <li>• FAX/databypass</li> <li>&gt; 711 pass through</li> </ul>	
	<ul style="list-style-type: none"> <li>• T38 FAX Relay</li> <li>&gt; Supports T.38 versions (06/98 to 03/02), V34 included.</li> <li>&gt; V.152 FAX</li> <li>&gt; T.38 over UDPTL - ASN.1 encoding/decoding of UDPTL packets (Packet loss, Recovery, Redundancy)</li> </ul>	
	<ul style="list-style-type: none"> <li>• RTP/RTCP transfer</li> <li>&gt; RTP/AVP - RFC3551 (formerly 1890)</li> <li>&gt; RTP/RTCP - RFC3550 (formerly 1889)</li> </ul>	

# DWR-956M Fibre/LTEAC1200 Gigabit Router with SIP, VoIP, VoLTE, CS& Fax

	<ul style="list-style-type: none"> <li>• Jitter Buffer               <ul style="list-style-type: none"> <li>&gt; Static /dynamic, up to 200ms</li> </ul> </li> </ul>
	<ul style="list-style-type: none"> <li>• Caller ID generation               <ul style="list-style-type: none"> <li>&gt; Support type 1 and type 2</li> <li>&gt; Format: Bellcore, ETSI FS</li> </ul> </li> </ul>
	<ul style="list-style-type: none"> <li>• Codec support</li> </ul>
	<ul style="list-style-type: none"> <li>&gt; G.711 A-Law</li> <li>&gt; G.711 U-Law</li> <li>&gt; G.722</li> <li>&gt; G.729 Annex A, B</li> </ul>
	<ul style="list-style-type: none"> <li>• Digital gain configuration               <ul style="list-style-type: none"> <li>&gt; Range: +/- 20db step by 0.5db</li> <li>&gt; The voice's volume controlled by the Host per channel</li> <li>&gt; On the fly modification</li> </ul> </li> </ul>
	<ul style="list-style-type: none"> <li>• Packet time length               <ul style="list-style-type: none"> <li>&gt; 10ms, 20ms, 30ms, 40ms</li> </ul> </li> </ul>
	<ul style="list-style-type: none"> <li>• Packet Loss Concealment               <ul style="list-style-type: none"> <li>&gt; Packet Loss Concealment - ITU-T G.711 Appendix I</li> </ul> </li> </ul>
	<ul style="list-style-type: none"> <li>• G.729 VAD&amp;CNG</li> </ul>
	<ul style="list-style-type: none"> <li>• G.711 VAD&amp;CNG               <ul style="list-style-type: none"> <li>&gt; Voice Activity Detector, Comfort Noise Generation - ITU-T G.711 Appendix II</li> <li>&gt; CNG RFC 3389</li> </ul> </li> </ul>
	<ul style="list-style-type: none"> <li>• DTMF generation &amp; detection               <ul style="list-style-type: none"> <li>&gt; ITU-T Q.23 and Q.24</li> <li>&gt; DTMF tones generation and detection compliant with the TIA 464B standard.</li> </ul> </li> </ul>
	<ul style="list-style-type: none"> <li>• Echo Canceller               <ul style="list-style-type: none"> <li>&gt; Echo canceller automatically enabled when both volume &lt;=36dBm</li> <li>&gt; Echo tail length (Up to 128ms)</li> <li>&gt; Echo canceller disabled by 2100Hz tone with phase reversal.</li> <li>&gt; Echo canceller must remove echo with ERL=0-3dB</li> <li>&gt; Line EC, G.168-2004 compliant</li> </ul> </li> </ul>
	<ul style="list-style-type: none"> <li>• Pulse Dial Detection</li> </ul>
	<ul style="list-style-type: none"> <li>• 3-Way conference</li> </ul>
	<ul style="list-style-type: none"> <li>• Tone generation               <ul style="list-style-type: none"> <li>&gt; Call progress tones generation</li> <li>&gt; Generate howler tones</li> <li>&gt; Quad tone generation</li> </ul> </li> </ul>
SIP / Call Control Feature List	<ul style="list-style-type: none"> <li>• SIP Protocol               <ul style="list-style-type: none"> <li>&gt; RFC 2617, HTTP Authentication: Basic and Digest Access Authentication.</li> <li>&gt; RFC 3428- Session Initiation Protocol (SIP) Extension for Instant Messaging</li> <li>&gt; RFC 3994- Indication of Message Composition for Instant Messaging</li> <li>&gt; RFC 2976- The SIP INFO Method</li> <li>&gt; RFC 3842-A Message Summary and Message Waiting Indication Event Package for the Session Initiation Protocol (SIP)</li> <li>&gt; RFC 2976, The SIP INFO Method</li> <li>&gt; RFC 3310-Hypertext Transfer Protocol (HTTP) Digest Authentication Using Authentication and Key Agreement (AKA)</li> <li>&gt; RFC 4169-Hypertext Transfer Protocol (HTTP) Digest Authentication Using Authentication and Key Agreement (AKA) Version-2</li> <li>&gt; RFC 4566 , SDP: Session Description Protocol (new)</li> <li>&gt; RFC 3264, An Offer-Answer Model with the SDP</li> <li>&gt; RFC 3265 - SIP- Specific Event Notification</li> <li>&gt; RFC 3311, The SIP UPDATE Method</li> <li>&gt; RFC 3842, - A Message Waiting Indication Event Package for the SIP</li> <li>&gt; RFC 3960, Early Media and Ringing Tone Generation in the SIP</li> </ul> </li> </ul>

# DWR-956M Fibre/LTE AC1200 Gigabit Router with SIP, VoIP, VoLTE, CS & Fax

	<ul style="list-style-type: none"> <li>&gt; RFC 3325, Private Extensions to the SIP for Asserted Identity within Trusted Networks (Partial)</li> <li>&gt; RFC 3261, SIP: Session Initiation Protocol version 2</li> <li>&gt; RFC 2327, SDP: Session Description Protocol</li> <li>&gt; RFC 3326, The Reason Header Field for SIP (Partial)</li> <li>&gt; RFC 3515, The SIP REFER Method</li> <li>&gt; RFC 3262, Reliability of Provisional Responses in the SIP</li> <li>&gt; RFC 3263, SIP: Locating SIP Servers</li> <li>&gt; RFC 3581, - An Extension to the SIP for Symmetric Response Routing</li> <li>&gt; RFC 4028, Session Timers in the SIP</li> <li>&gt; RFC 4566 - SDP Session Description Protocol</li> <li>&gt; RFC 4488- Suppression of Session Initiation Protocol (SIP) REFER Method Implicit Subscription</li> <li>&gt; RFC 3966 -The tel URI for Telephone Numbers</li> <li>&gt; RFC 4028-Session Timers in the Session Initiation Protocol (SIP)</li> <li>&gt; RFC 3093- Session Initiation Protocol (SIP) Extension for Event State Publication</li> <li>&gt; RFC 3605- Real Time Control Protocol (RTCP) attribute in Session Description Protocol (SDP)</li> <li>&gt; RFC 3608, Session Initiation Protocol (SIP) Extension Header Field for Service Route Discovery During Registration</li> <li>&gt; RFC 3327 Session Initiation Protocol (SIP) Extension Header Field for Registering Non-Adjacent Contacts</li> <li>&gt; RFC 3891 The Session Initiation Protocol (SIP) "Replaces" Header</li> <li>&gt; RFC 3892 The Session Initiation Protocol (SIP) Referred-By Mechanism</li> <li>&gt; RFC 3420 Internet Media Type message/sipfrag</li> <li>&gt; RFC 2046- Multipurpose Internet Mail Extensions (MIME) Part Two: Media Types</li> <li>&gt; RFC 5621- Message Body Handling in the Session Initiation Protocol (SIP)</li> <li>&gt; RFC 4320-Actions Addressing Identified Issues with the Session Initiation Protocol's (SIP) Non-INVITE Transaction</li> <li>&gt; RFC 4321-Problems Identified Associated with the Session Initiation Protocol's (SIP) Non-INVITE Transaction</li> <li>&gt; RFC 5057-Multiple Dialog Usages in the Session Initiation Protocol</li> <li>&gt; RFC 4475-Session Initiation Protocol (SIP) Torture Test Messages</li> <li>&gt; RFC 5621-Message Body Handling in the Session Initiation Protocol (SIP)</li> <li>&gt; RFC 2833 - RTP Payload for DTMF Digits, Telephony Tones and Telephony Signals</li> <li>&gt; IETF RFC 3310 HTTP Digest Authentication using Authentication and Key Agreement (AKA) when talking with the registration server.</li> <li>&gt; IETF RFC 3311 The Session Initiation Protocol (SIP) UPDATE Method.</li> <li>&gt; IETF RFC 2198 The redundancy function, RTP Payload for Redundant Audio Data</li> <li>&gt; IETF RFC 3555 MIME Type Registration of RTP Payload Formats</li> <li>&gt; IETF RFC 3388 Grouping of Media Lines in the Session Description Protocol (SDP)</li> <li>&gt; IETF RFC 3489 STUN - Simple Traversal of User Datagram Protocol (UDP) Through Network Address Translators (NATs).</li> </ul>
	<ul style="list-style-type: none"> <li>• WMI (Support SIP Stack)</li> </ul>
	<ul style="list-style-type: none"> <li>• Call Feature</li> <li>&gt; Busy Call Forward</li> <li>&gt; Attended Call Transfer</li> <li>&gt; Do not Disturb</li> <li>&gt; Speed dial Number</li> <li>&gt; Call waiting</li> <li>&gt; 3-Way conference</li> <li>&gt; No Reply Call Forward</li> <li>&gt; Blind Call Transfer</li> <li>&gt; Unconditional Call Forward</li> <li>&gt; Hot line</li> <li>&gt; A digit map of at least 256 characters.</li> <li>&gt; Draft-rosenberg-midcom-turn-08, Traversal Using Relay NAT (TURN).</li> </ul>
Dimensions	<ul style="list-style-type: none"> <li>• 210x150x37 mm (8.26x5.91x1.46 inches)</li> </ul>
Weight	<ul style="list-style-type: none"> <li>• -20 °C ~ 85 °C</li> </ul>
Power	<ul style="list-style-type: none"> <li>• Input: 100 ~ 240V</li> <li>• Output: 12 V / 1.5 A</li> </ul>
Temperature	<ul style="list-style-type: none"> <li>• Operating: 0 to 45 °C (32 to 113 °F)</li> <li>• Storage: -20 to 70 °C (-4 to 158 °F)</li> </ul>
Humidity	<ul style="list-style-type: none"> <li>• 10% ~ 95% non-condensing</li> </ul>
Certifications	<ul style="list-style-type: none"> <li>• CE</li> <li>• FCC</li> <li>• LVD</li> <li>• RCM</li> </ul>
Part Number	Description
DWR-956M	Fibre/LTE AC1200 GE Router with VoIP, VoLTE, CS & Fax